

## TR12A

SINGLE 12" FULL RANGE SPEAKER

### SPECIFICATIONS

Frequency Response	75 Hz - 20 kHz (-10 dB)
Dispersion (H)	100° x 55° Rotatable
Sensitivity	97 dB
SPL	120 dB (Continuous) / 128 dB (Peak)
Power Rating (AES)	300 W
Nominated Impedance	8 ohm
HF Drivers	Ferrite, 1 x 1" tweeter / 44 mm Voice Coil
MF Drivers	-
LF Drivers	Ferrite, 1 x 12" Ferrite / 65 mm Voice Coil
Amplifier	300W/8 ohm
Connectors	XLR input and output, PowerCon input and output
Painting	Black water-based paint
Dimensions (W x D x H)	368 x 313 x 585 mm
Net Weight	20 kg



## TR18BA

SINGLE 18-INCH ULTRA-LOW SPEAKERS

### SPECIFICATIONS

Frequency Response	30 Hz - 200 kHz
Dispersion (H)	-
Sensitivity	99 dB
SPL	126 dB (continuous), 132 dB (peak)
Power Rating (AES)	600 W
Nominated Impedance	8 ohm
HF Drivers	-
MF Drivers	-
LF Drivers	1 x 18" Ferrite Woofer / 100mm Voice Coil
Power Output	800W / 8 ohm
Box Treatment	Black waterborne paint
Dimensions (W x D x H)	330 x 255 x 500 mm
Net Weight	30 kg

